

Safety Data Sheet Spartan Chemical Company, Inc.

Revision Date: 11-Aug-2015

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name:

CHEWING GUM REMOVER

Product Number:

Recommended Use: C

Uses Advised Against:

Chewing gum remover

For Industrial and Institutional Use Only

Manufacturer/Supplier:

Spartan Chemical Company, Inc.

1110 Spartan Drive Maumee, Ohio 43537 USA 800-537-8990 (Business hours) www.spartanchemical.com

24 Hour Emergency Phone Numbers:

Medical Emergency/Information: 888-314-6171

Transportation/Spill/Leak:

CHEMTREC 800-424-9300

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable Aerosols Gases Under Pressure Category 1 Liquefied gas

GHS Label Elements

Signal Word:

Symbols:

Danger



Hazard Statements:

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated

Precautionary Statements:

Prevention:

Keep away from heat/sparks/open flames/hot surfaces. — No smoking

Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even after use

Intentional misuse by deliberately concentrating and inhaling contents may be harmful or

fatal.

Response:

-Specific Treatment:

See Safety Data Sheet Section 4: "FIRST AID MEASURES" for additional information.

Storage:

Protect from sunlight, Do not expose to temperatures exceeding 50 °C/122 °F Protect from

sunlight. Store in a well-ventilated place

Disposal:

Not Applicable

Hazards Not Otherwise Classified:

Not Applicable

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH
ргорапе	TWA: 1000 ppm	TWA: 1000 ppm	IDLH: 2100 ppm
74-98-6		TWA: 1800 mg/m ³	TWA: 1000 ppm
		(vacated) TWA: 1000 ppm	TWA: 1800 mg/m ³
		(vacated) TWA: 1800 mg/m ³	
N-butane	TWA: 1000 ppm	(vacated) TWA: 800 ppm	TWA: 800 ppm
106-97-8		(vacated) TWA: 1900 mg/m ³	TWA: 1900 mg/m ³

Engineering Controls:

Provide good general ventilation.

If work practices generate dust, fumes, gas, vapors or mists which expose workers to chemicals above the occupational exposure limits, local exhaust ventilation or other

Revision Date: 11-Aug-2015

engineering controls should be considered.

Personal Protective Equipment

Eye/Face Protection:

Skin and Body Protection: Respiratory Protection:

Not required with expected use. Not required with expected use.

Not required with expected use.

If occupational exposure limits are exceeded or respiratory irritation occurs, use of a NIOSH/MSHA approved respirator suitable for the use-conditions and chemicals in Section

3 should be considered.

General Hygiene Considerations:

Wash hands and any exposed skin thoroughly after handling.

See 29 CFR 1910.132-138 for further guidance.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical State:	Aerosol	
Color:	Colorless	
Odor:	Odorless	
pH:	Not applicable	
Melting Point / Freezing Point:	No information available.	
Boiling Point / Boiling Range:	< -18 °C / 0 °F	
Flash Point:	< -18 °C / < 0 °F (Propellant-estimated)	
Evaporation Rate:	> 1 (Butyl acetate = 1)	
Flammability (solid, gas)	No information available.	
Upper Flammability Limit:	No information available.	
Lower Flammability Limit:	No information available.	
Vapor Pressure:	No information available.	
Vapor Density:	No information available.	
Specific Gravity:	0.543	
Solubility(ies):	No information available.	
Partition Coefficient:	No information available.	
Autoignition Temperature:	No information available.	
Decomposition Temperature:	No information available.	
Viscosity:	No information available.	

10. STABILITY AND REACTIVITY

Reactivity:

This material is considered to be non-reactive under normal conditions of use.

Chemical Stability:

Stable under normal conditions.

Conditions to Avoid:

Possibility of Hazardous Reactions: Not expected to occur with normal handling and storage.

Incompatible Materials:

Extremes of temperature and direct sunlight.

Strong oxidizing agents. Strong acids.

Hazardous Decomposition

May include carbon monoxide, carbon dioxide (CO2) and other toxic gases or vapors.

Products:

11. TOXICOLOGICAL INFORMATION

Likely Routes of Exposure:

Symptoms of Exposure:

Eyes, Skin, Ingestion, Inhalation.

-Eye Contact:

Contact with product may cause frostbite

Page 3 / 5

Revision Date: 11-Aug-2015

Chronic Health Hazard:

No

Fire Hazard:

Yes

Sudden release of pressure hazard:

Yes

Reactive Hazard:

No

California Proposition 65

This product is not subject to warning requirements under California Proposition 65.

16. OTHER INFORMATION

NFPA

Health Hazards: 1

Flammability: 4

Instability: 0

Special: N/A

HMIS

Health Hazards: 1

Flammability: 4

Physical Hazards: 2

Revision Date:

11-Aug-2015

Reasons for Revision:

Section 14 and 15

Disclaimer:

The information provided in this Material Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

Page 5/5